



Tipo Type	Dimensioni - Dimensions											Bull. fess. Bolt Size	Coefficients di carico (N) Load ratings (N)		Cuscinetto Bearing	Supporto Housing	Peso Weight	
	d	a	e	i	g	l	s	z	t	B	n		Dinamico C Dynamic C	Statico Co Static Co				kg
	mm/inch												mm/inch					
UCF201 UCF201-8	12 3/4	86 3 3/8	64 2 3/4	15 1 1/2	12 1 1/2	25,5 1	12 1 1/2	33,3 1 1/4	37,5 1 3/4	31 1,2205	12,7 0,500	M10 3/8	12160	6318	UC201 UC201-8	F204	0,60 0,59	
UCF202 UCF202-9 UCF202-10	15 9/8 5/8	86 3 3/8	64 2 3/4	15 1 1/2	12 1 1/2	25,5 1	12 1 1/2	33,3 1 1/4	37,5 1 3/4	31 1,2205	12,7 0,500	M10 3/8	12160	6318	UC202 UC202-9 UC202-10	F204	0,59 0,59 0,59	
UCF203 UCF203-11	17 1 1/8	86 3 3/8	64 2 3/4	15 1 1/2	12 1 1/2	25,5 1	12 1 1/2	33,3 1 1/4	37,5 1 3/4	31 1,2205	12,7 0,500	M10 3/8	12160	6318	UC203 UC203-11	F204	0,58 0,57	
UCF204 UCF204-12	20 3/4	86 3 3/8	64 2 3/4	15 1 1/2	12 1 1/2	25,5 1	12 1 1/2	33,3 1 1/4	37,5 1 3/4	31 1,2205	12,7 0,500	M10 3/8	12160	6318	UC204 UC204-12	F204	0,56 0,56	
UCF205 UCF205-13 UCF205-14 UCF205-15 UCF205-16	25 1 5/8 7/8 1 1/8	95 3 3/4	70 2 3/4	16 5/8	14 3/4	27 1 1/4	12 1 1/2	35,8 1 1/2	40 1 3/4	34,1 1,3425	14,3 0,563	M10 3/8	13300	7457	UC205 UC205-13 UC205-14 UC205-15 UC205-16	F205	0,80 0,84 0,83 0,81 0,80	
UCF206 UCF206-17 UCF206-18 UCF206-19 UCF206-20	30 1 1/8 1 1/8 1 3/16	108 4 1/4	83 3 1/4	18 4 5/8	14 3 5/8	31 1 1/2	12 1 1/2	40,2 1 1/2	44,5 1 3/4	38,1 1,5000	15,9 0,626	M10 3/8	18525	10735	UC206 UC206-17 UC206-18 UC206-19 UC206-20	F206	1,12 1,15 1,14 1,12 1,11	
UCF207 UCF207-20 UCF207-21 UCF207-22 UCF207-23	35 1 1/4 1 5/8 1 3/8	117 4 3/8	92 3 5/8	19 3/4	16 5/8	34 1 1/2	14 3 5/8	44,4 1 3/4	48,5 1 29/32	42,9 1,6890	17,5 0,689	M12 7/16	24415	14630	UC207 UC207-20 UC207-21 UC207-22 UC207-23	F207	1,46 1,52 1,49 1,46 1,43	
UCF208 UCF208-24 UCF208-25	40 1 1/2 1 5/8	130 5 1/8	102 4 1/4	21 5 3/8	16 5/8	36 1 27/64	16 5/8	51,2 2 1/4	55,5 2 1/8	49,2 1,9370	19 0,748	M14 1/2	27645	16910	UC208 UC208-24 UC208-25	F208	1,84 1,88 1,85	
UCF209 UCF209-26 UCF209-27 UCF209-28	45 1 3/8 1 11/16 1 3/4	137 5 1/2	105 4 1/4	22 5 5/8	18 2 3/8	38 1 1/2	16 5/8	52,2 2 1/8	56,5 2 1/4	49,2 1,9370	19 0,748	M14 1/2	32395	20235	UC209 UC209-26 UC209-27 UC209-28	F209	2,15 2,25 2,21 2,17	
UCF210 UCF210-29 UCF210-30 UCF210-31 UCF210-32	50 1 13/16 1 7/8 1 15/16	143 5 5/8	111 4 3/8	22 5 5/8	18 2 3/8	40 1 5/8	16 5/8	54,6 2 1/8	59,5 2 1/2	51,6 2,0315	19 0,748	M14 1/2	33345	22135	UC210 UC210-29 UC210-30 UC210-31 UC210-32	F210	2,42 2,54 2,49 2,44 2,40	
UCF211 UCF211-32 UCF211-33 UCF211-34 UCF211-35	55 2 2 1/8 2 1/8 2 3/8	162 6 3/8	130 5 1/8	25 6 3/8	20 2 5/8	43 1 11/16	19 3/4	58,4 1 5/8	63 2 3/8	55,6 2,1890	22,2 0,874	M16 5/8	41230	27930	UC211 UC211-32 UC211-33 UC211-34 UC211-35	F211	3,31 3,46 3,40 3,35 3,29	
UCF212 UCF212-36 UCF212-37 UCF212-38 UCF212-39	60 2 1/4 2 5/8 2 3/8	175 6 5/8	143 5 5/8	29 1 1/4	20 2 5/8	48 1 57/64	19 3/4	68,7 2 45/64	73,5 2 57/64	65,1 2,5630	25,4 1,000	M16 5/8	49780	34390	UC212 UC212-36 UC212-37 UC212-38 UC212-39	F212	4,28 4,41 4,33 4,26 4,19	
UCF213 UCF213-40 UCF213-41	65 2 1/2 2 9/16	187 7 23/64	149 5 33/64	30 1 3/16	22 5/8	50 1 31/32	19 3/4	69,7 2 3/4	74,5 2 13/16	65,1 2,5630	25,4 1,000	M16 5/8	54340	38095	UC213 UC213-40 UC213-41	F213	4,99 5,08 4,99	
UCF214 UCF214-42 UCF214-43 UCF214-44	70 2 5/8 2 11/16 2 3/4	193 7 11/32	152 5 9/64	31 1 1/2	22 5/8	54 2 1/8	19 3/4	75,4 2 29/32	81,5 3 13/64	74,6 2,9370	30,2 1,189	M16 5/8	59090	41895	UC214 UC214-42 UC214-43 UC214-44	F214	5,85 6,06 5,96 5,86	
UCF215 UCF215-45 UCF215-46 UCF215-47 UCF215-48	75 2 13/16 2 7/8 2 15/16	200 7 7/8	159 6 11/64	34 1 1/2	22 5/8	56 2 1/2	19 3/4	78,5 3 3/32	83,5 3 3/32	77,8 3,0630	33,3 1,311	M16 5/8	64030	45885	UC215 UC215-45 UC215-46 UC215-47 UC215-48	F215	6,91 7,16 7,05 6,94 6,82	
UCF216 UCF216-49 UCF216-50 UCF216-51	80 3 1/8 3 3/8 3 3/8	208 8 3/8	165 6 1/2	34 1 1/2	22 5/8	58 2 9/32	23 2 9/32	83,3 3 3/32	88,5 3 39/64	82,6 3,2520	33,3 1,311	M20 3/4	69065	50350	UC216 UC216-49 UC216-50 UC216-51	F216	7,50 7,68 7,55 7,42	
UCF217 UCF217-52 UCF217-53 UCF217-55	85 3 1/4 3 3/8 3 7/8	220 8 21/32	175 6 37/64	36 1 1/4	24 1 1/8	63 2 15/32	23 2 9/32	87,6 3 1/16	92,6 3 41/64	85,7 3,3740	34,1 1,343	M20 3/4	79800	58805	UC217 UC217-52 UC217-53 UC217-55	F217	9,66 9,88 9,74 9,45	
UCF218 UCF218-56	90 3 1/2	235 9 1/4	187 7 7/16	40 1 3/4	24 1 1/8	68 2 11/16	23 2 9/32	96,3 3 29/32	101,5 4	96 3,7795	39,7 1,5630	M20 3/4	91295	67925	UC218 UC218-56	F218	12,06 12,17	

Disponibile in acciaio inox Supporto: AISI 304 - Cuscinetto: AISI 440C o 420C - Available stainless steel Housing: AISI 304 - Bearing: AISI 440C or 420C
Disponibile su richiesta con cuscinetto SA (SAF.) - Available under request with SA bearing (SAF.)