

### Broca espiral HPC, 25 x D

Continuado de la página anterior

Ø h7 mm	Longitud de la espiral mm	Longitud total mm	Ø de vástago mm	format EGT		Ref.
				ACERO	1214	
				< 1400 N/mm <sup>2</sup>	SUPRA	
				f	€	
				mm/rev		
4.8	140.5	190	6	0.1	527,24	...0480
5	140.5	190	6	0.1	527,24	...0500
5.5	160.5	210	6	0.1	538,44	...0550
5.8	160.5	210	6	0.1	538,44	...0580
6	170.5	220	6	0.1	538,44	...0600
6.5	191	230	8	0.1	602,46	...0650
6.8	191	230	8	0.1	602,46	...0680
7	201	240	8	0.1	602,46	...0700
7.5	214	250	8	0.1	602,46	...0750
7.8	224	260	8	0.1	636,31	...0780
8	224	260	8	0.1	636,31	...0800
8.5	237	280	10	0.1	799,06	...0850

(W111)

Ø h7 mm	Longitud de la espiral mm	Longitud total mm	Ø de vástago mm	format EGT		Ref.
				ACERO	1214	
				< 1400 N/mm <sup>2</sup>	SUPRA	
				f	€	
				mm/rev		
8.8	247	290	10	0.1	803,31	...0880
9	247	290	10	0.1	803,31	...0900
9.5	267	310	10	0.18	835,02	...0950
9.8	267	310	10	0.18	835,02	...0980
10	267	310	10	0.18	835,02	...1000
10.2	292	340	12	0.18	1.268,38	...1020
10.8	302	350	12	0.18	1.268,38	...1080
11.8	327	375	12	0.18	1.268,38	...1180
12	327	375	12	0.18	1.268,38	...1200

(W111)

### Broca espiral HPC, 30 x D

Características: Broca espiral estable, multigeometría especial, con cámaras de virutas pulidas.

Metal  
duro  
integral

UNI

135°

30°

DIN  
6535-HA

30xD

HPC



Aplicación	ACERO			INOX			FUNDICIÓN		ALEACIONES ESPECIALES		METALES NO FÉRRICOS			ACERO TEMPLADO			Ref.
	< 700 N/mm <sup>2</sup>	< 1000 N/mm <sup>2</sup>	< 1400 N/mm <sup>2</sup>	Ferrit./ martens.	Aus-tenítico	Duplex	GG/ GTS	GGG	Titanio > 850 N/mm <sup>2</sup>	Alumi-nio < 8% Si	Alumi-nio > 8% Si	Aleaciones de cobre y cinc	GFRP/CFRP/ Duropl.	< 55 HRC	< 60 HRC	> 60 HRC	
V <sub>c</sub> [m/min]	50	45	40	-	30	-	40	40	-	-	-	-	-	-	-	-	1216

Ø h7 mm	Longitud de la espiral mm	Longitud total mm	Ø de vástago mm	format EGT		Ref.
				ACERO	1216	
				< 1400 N/mm <sup>2</sup>	SUPRA	
				f	€	
				mm/rev		
2	65.5	105	4	0.05	290,66	...0200
2.2	75.5	115	4	0.05	290,66	...0220
2.3	75.5	115	4	0.05	290,66	...0230
2.4	85.5	130	4	0.05	290,66	...0240
2.5	85.5	130	4	0.05	290,66	...0250
2.7	95.5	140	4	0.05	290,66	...0270
2.8	95.5	140	4	0.05	290,66	...0280
2.9	95.5	140	4	0.05	290,66	...0290
3	105.5	150	6	0.05	541,21	...0300
3.2	105.5	150	6	0.1	541,21	...0320
3.3	115.5	160	6	0.1	566,52	...0330
3.5	115.5	160	6	0.1	566,52	...0350
3.8	125.5	175	6	0.1	566,52	...0380
4	135.5	185	6	0.1	579,22	...0400
4.2	135.5	185	6	0.1	579,22	...0420
4.5	145.5	195	6	0.1	579,22	...0450
4.6	155.5	205	6	0.1	579,22	...0460
4.8	165.5	210	6	0.1	604,60	...0480

(W111)

Ø h7 mm	Longitud de la espiral mm	Longitud total mm	Ø de vástago mm	format EGT		Ref.
				ACERO	1216	
				< 1400 N/mm <sup>2</sup>	SUPRA	
				f	€	
				mm/rev		
5	165.5	210	6	0.1	604,60	...0500
5.5	180.5	240	6	0.1	623,64	...0550
5.8	190.5	240	6	0.1	623,64	...0580
6	190.5	240	6	0.1	623,64	...0600
6.5	222	260	8	0.1	682,82	...0650
6.8	222	260	8	0.1	682,82	...0680
7	232	270	8	0.1	729,32	...0700
7.5	252	290	8	0.1	729,32	...0750
7.8	262	300	8	0.1	737,81	...0780
8	267	305	8	0.1	737,81	...0800
8.5	278	320	10	0.1	1.021,02	...0850
8.8	298	340	10	0.1	1.021,02	...0880
9	298	340	10	0.1	1.021,02	...0900
9.5	316	360	10	0.18	1.021,02	...0950
9.8	338	380	10	0.18	1.021,02	...0980
10	338	380	10	0.18	1.021,02	...1000

(W111)