

Fresa frontal, 45°

Ø D mm	Z	Ø d g7 mm	L mm	l mm	Ø D1 mm	a _p máx. mm	Plaquita de corte	format	
								2999	Ref.
20	2	20	82	32	29,8	4,5	SEMT 09T3...	247,60	...0200
25	3	25	98	42	34,8	4,5	SEMT 09T3...	270,97	...0205
32	4	32	102	42	42	4,5	SEMT 09T3...	358,27	...0210

format

2999

Ref.

€

247,60

270,97

358,27

(W280)



format
professional quality



Suministro sin plaquitas de corte.

Fresa de planear, 45°

Ø D mm	Z	Ø d H7 mm	Ø d1 mm	L mm	Ø D1 mm	a _p máx. mm	Plaquita de corte	format	
								2999	Ref.
50	5	22	18	40	59,6	4,5	SEMT 09T3...	401,67	...0225
63	6	22	18	40	75,8	4,5	SEMT 09T3...	401,67	...0230
80	8	27	38	50	89,6	4,5	SEMT 09T3...	489,27	...0235
100	10	32	45	50	110	4,5	SEMT 09T3...	632,74	...0240

format

2999

Ref.

€

401,67

401,67


489,27

632,74

(W280)



format
professional quality



Suministro sin plaquitas de corte.

Pieza de recambio

Características	U.E.	format		Wera	Ref.
		2999	5886		
Tornillo	10 Δ	6,66	-	-	...0005
Destornillador T9 x 60 mm	1	-	10,59	-	...0035

Δ Solo es posible la entrega de una unidad de embalaje completa.

format

2999

5886

Ref.

€

6,66

-

10,59

(W281)

(W543)



Tornillo



Destornillador

Plaquita de corte ISO



format
professional quality

Designación ISO	Tipo de material de corte	Velocidad de corte Avance Profundidad de corte	format							U.E.	format	
			P	M	K	N	S	H	2999		Ref.	
SEMT 09T3AFSN-F	PMK 9130	v _c m/min f _z mm a _p mm	190-325 0,12-0,35 0,5-4,5	110-195 0,12-0,26 0,5-3,4	180-305 0,12-0,35 0,5-4,5	- - -	- - -	- - -	10 Δ	12,02	...5000	
SEMT 09T3AFSN-F	U 9145	v _c m/min f _z mm a _p mm	150-240 0,12-0,35 0,5-4,5	90-140 0,12-0,26 0,5-3,4	140-225 0,12-0,35 0,5-4,5	- - -	30-70 0,12-0,21 0,5-2,7	- - -	10 Δ	12,46	...5003	

Δ Solo es posible la entrega de una unidad de embalaje completa.

format

2999

Ref.

€

12,02

12,46

(W282)