

Cabezal portacuchillas angular, 90°

Ø D mm	Z	Ø d H7 mm	Ø d1 mm	L mm	a _p máx. mm	Plaquita de corte	format		
							2999	Ref.	
50	5	22	18	40	10	SDMT 1205...	€	...	
63	6	22	18	40	10	SDMT 1205...	364,79	...0400	
80	6	27	38	50	10	SDMT 1205...	417,33	...0405	
100	8	32	45	50	10	SDMT 1205...	456,54	...0410	
125	9	40	56	63	10	SDMT 1205...	552,21	...0415	
							773,75	...0420	
							(W280)		



format
professional quality



Suministro sin plaquitas de corte.

2.1

Pieza de recambio

Características	U.E.	format		Ref.
		2999	5886	
Tornillo	10 Δ	€	€	...
Destornillador T15 x 80 mm	1	8,41	-	...0045
		-	10,90	...0050
		(W281)	(W543)	

Δ Solo es posible la entrega de una unidad de embalaje completa.



Tornillo



Destornillador

Plaquita de corte ISO



format
professional quality

Designación ISO	Tipo de material de corte	Velocidad de corte Avance Profundidad de corte	P	M	K	N	S	H	U.E.	format	
										Acero	Inoxidable
SDMT 120508SR-F	PMK 9130 	v _c m/min f _z mm a _p mm	180-275 0,1-0,25 1-10	105-165 0,1-0,19 1-7,5	170-260 0,1-0,25 1-10	270-960 0,1-0,25 1-10	35-80 0,1-0,15 1-6	- - -	10 Δ	€	...
SDMT 120508SR-F	U 9145 	v _c m/min f _z mm a _p mm	165-225 0,1-0,25 1-10	95-135 0,1-0,19 1,0-7,5	155-210 0,1-0,25 1-10	- - -	30-65 0,1-0,15 1-6	- - -	10 Δ	16,14	...5061
SDMT 120508SR-M	KNH 9110 	v _c m/min f _z mm a _p mm	155-240 0,1-0,25 1-10	90-140 0,1-0,19 1-7,5	145-225 0,1-0,25 1-10	- - -	30-70 0,1-0,15 1-6	30-45 0,1-0,2 0,3-1,5	10 Δ	16,39	...5062
SDMT 120508SR-M	PMK 9130 	v _c m/min f _z mm a _p mm	145-230 0,1-0,25 1-10	85-135 0,1-0,19 1-7,5	135-215 0,1-0,25 1-10	- - -	25-65 0,1-0,15 1-6	25-45 0,1-0,2 0,3-1,5	10 Δ	16,39	...5063
SDMT 120508SR-M	U 9145 	v _c m/min f _z mm a _p mm	145-225 0,1-0,25 1-10	85-135 0,1-0,19 1-7,5	135-210 0,1-0,25 1-10	- - -	25-65 0,1-0,15 1-6	- - -	10 Δ	16,39	...5066
SDMT 120508SR-M	U 9145 	v _c m/min f _z mm a _p mm	145-225 0,1-0,25 1-10	85-135 0,1-0,19 1-7,5	135-210 0,1-0,25 1-10	- - -	25-65 0,1-0,15 1-6	- - -	10 Δ	16,39	...5069
SDMT 120508SR-R	PMK 9130 	v _c m/min f _z mm a _p mm	190-285 0,2-0,45 1-10	110-170 0,2-0,34 1-7,5	180-270 0,2-0,45 1-10	- - -	35-85 0,2-0,27 1-6	- - -	10 Δ	16,39	...5067

Δ Solo es posible la entrega de una unidad de embalaje completa.

(W282)

Fresa frontal, 90°

Ø D mm	Z	Ø d g7 mm	L mm	l mm	a _p máx. mm	Plaquita de corte	format		
							2999	Ref.	
20	2	20	82	32	8	SOMT 09T3...	€	...	
25	3	25	98	38	8	SOMT 09T3...	247,60	...0330	
32	4	32	104	42	8	SOMT 09T3...	270,97	...0335	
							358,27	...0340	
							(W280)		



format
professional quality



Suministro sin plaquitas de corte.