

Cabezal portacuchillas angular, 90°

| Ø D mm | Z | Ø d H7 mm | Ø d ₁ mm | L mm | a _p máx. mm | Plaquita de corte | format | |
|-----------|---|--------------|------------------------|---------|---------------------------|-------------------|----------|---------|
| | | | | | | | 2999 | Ref. |
| 40 | 5 | 16 | 14 | 40 | 8 | SOMT 09T3... | € 322,98 | ...0345 |
| 50 | 6 | 22 | 18 | 40 | 8 | SOMT 09T3... | € 347,52 | ...0350 |
| 63 | 7 | 22 | 18 | 40 | 8 | SOMT 09T3... | € 404,59 | ...0355 |

(W280)



format
professional quality



Suministro sin plaquitas de corte.

Pieza de recambio

| Características | U.E. | format | | Ref. |
|---------------------------|------|--------|-----------|---------|
| | | 2999 | Wera 5886 | |
| Tornillo | 5 Δ | € 8,41 | – | ...0032 |
| Destornillador T9 x 60 mm | 1 | – | € 10,59 | ...0035 |

(W281) (W543)



Tornillo



Destornillador

Δ Solo es posible la entrega de una unidad de embalaje completa.

Plaquita de corte ISO



format
professional quality

| Designación ISO | Tipo de material de corte | Velocidad de corte Avance Profundidad de corte | format | | | | | U.E. | 2999 | | |
|-----------------|---------------------------|--|-----------|-----------|-----------|-----------|-----------|------|------|---------|---------|
| | | | P | M | K | N | S | | H | € | Ref. |
| SOMT 09T304-F | KH 9105 | v _c m/min | 115–220 | 65–130 | 105–205 | 170–770 | 20–65 | – | 10 Δ | € 13,66 | ...5042 |
| | | f _z mm | 0,08–0,35 | 0,08–0,26 | 0,08–0,35 | 0,08–0,35 | 0,08–0,21 | – | | | |
| | | a _p mm | 0,5–8 | 0,5–6 | 0,5–8 | 0,5–8 | 0,5–4,8 | – | | | |
| SOMT 09T304-F | PMK 9130 | v _c m/min | 115–215 | 65–125 | 105–200 | – | – | – | 10 Δ | € 14,35 | ...5045 |
| | | f _z mm | 0,08–0,35 | 0,08–0,26 | 0,08–0,35 | – | – | – | | | |
| | | a _p mm | 0,5–8 | 0,5–6 | 0,5–8 | – | – | – | | | |
| SOMT 09T304-F | U 9145 | v _c m/min | 110–200 | 65–120 | 100–190 | – | 20–60 | – | 10 Δ | € 13,66 | ...5060 |
| | | f _z mm | 0,08–0,35 | 0,08–0,26 | 0,08–0,35 | – | 0,08–0,21 | – | | | |
| | | a _p mm | 0,5–8 | 0,5–6 | 0,5–8 | – | 0,5–4,8 | – | | | |
| SOMT 09T304-M | PMK 9130 | v _c m/min | 115–215 | 65–125 | 105–200 | – | – | – | 10 Δ | € 14,13 | ...5051 |
| | | f _z mm | 0,08–0,35 | 0,08–0,26 | 0,08–0,35 | – | – | – | | | |
| | | a _p mm | 0,5–8 | 0,5–6 | 0,5–8 | – | – | – | | | |
| SOMT 09T304-M | U 9145 | v _c m/min | 110–200 | 65–120 | 100–190 | – | 20–60 | – | 10 Δ | € 14,35 | ...5054 |
| | | f _z mm | 0,08–0,35 | 0,08–0,26 | 0,08–0,35 | – | 0,08–0,21 | – | | | |
| | | a _p mm | 0,5–8 | 0,5–6 | 0,5–8 | – | 0,5–4,8 | – | | | |

(W282)

Δ Solo es posible la entrega de una unidad de embalaje completa.


Fresa para desbarbar y centrar, 45°

| Ø D mm | Z | Ø d g7 mm | L mm | l mm | l ₁ mm | a _p máx. mm | Plaquita de corte | format | |
|-----------|---|--------------|---------|---------|----------------------|---------------------------|-------------------|----------|---------|
| | | | | | | | | 2999 | Ref. |
| 12 | 1 | 12 | 90 | 60 | 6,5 | 6 | SDET 0825... | € 134,02 | ...1750 |

(W280)

DIN
1835 B

format
professional quality



Suministro sin plaquitas de corte.