

Pieza de recambio

Características	U.E.	format		Ref.
		2999	5886	
		€	€	
Tornillo interior/exterior para Ø 15-17 mm	10 Δ	6,16	-	...0172
Tornillo interior para Ø 18-19 mm	10 Δ	6,40	-	...0174
Tornillo exterior para Ø 18-19 mm	10 Δ	6,16	-	...0172
Tornillo interior para Ø 20-21 mm	10 Δ	6,40	-	...0174
Tornillo interior/exterior para Ø 22 mm	10 Δ	6,40	-	...0050
Tornillo interior para Ø 23-26 mm	10 Δ	6,40	-	...0180
Tornillo exterior para Ø 23-26 mm	10 Δ	6,66	-	...0005
Tornillo interior/exterior Ø 27 mm	10 Δ	6,66	-	...0005
Tornillo interior Ø 28-30 mm	10 Δ	6,66	-	...0005
Tornillo exterior para Ø 28-30 mm	10 Δ	6,66	-	...0182
Tornillo interior para Ø 32-34 mm	10 Δ	13,27	-	...0185
Tornillo exterior para Ø 32-34 mm	10 Δ	6,66	-	...0184
Tornillo interior para Ø 36-40 mm	10 Δ	A consultar	-	...0185
Tornillo exterior para Ø 36-40 mm	10 Δ	8,47	-	...0188
Destornillador para Ø 15-22 mm T7 x 60 mm	1	-	10,59	...0020
Destornillador para Ø 23-26 mm T8 x 60 mm	1	-	10,59	...0030
Destornillador para Ø 27-30 mm T9 x 60 mm	1	-	10,59	...0035
Destornillador para Ø 32-40 mm T15 x 80 mm	1	-	10,90	...0050

Δ Solo es posible la entrega de una unidad de embalaje completa.

(W281)

(W543)



Tornillo



Destornillador

Plaquita de corte ISO



XPET - interior



SCET - exterior



Designación ISO	Tipo de material de corte	Velocidad de corte Avance	format					U.E.	2999	Ref.	
			P	M	K	N	S				H
			acero	inoxidable	fundición	aluminio	superalac.	templado	€		
XPET 0602AP	9145 	v _c m/min f mm/rev.	140-240 0,04-0,15	80-140 0,06-0,11	130-225 0,06-0,15	- -	- -	- -	10 Δ	14,54	...5803
XPET 0703AP	9145 	v _c m/min f mm/rev.	140-240 0,07-0,18	80-140 0,07-0,14	130-225 0,07-0,18	- -	- -	- -	10 Δ	15,34	...5806
XPET 11T3AP	9145 	v _c m/min f mm/rev.	140-240 0,09-0,22	80-140 0,09-0,17	130-225 0,09-0,22	- -	- -	- -	10 Δ	17,95	...5812
SCET 050204	UD 9035 	v _c m/min f mm/rev.	140-240 0,05-0,11	80-140 0,05-0,08	130-225 0,05-0,11	- -	- -	- -	10 Δ	13,68	...5818
SCET 060204	UD 9035 	v _c m/min f mm/rev.	140-240 0,06-0,15	80-140 0,06-0,11	130-225 0,06-0,15	- -	- -	- -	10 Δ	14,54	...5821
SCET 070308	UD 9035 	v _c m/min f mm/rev.	140-240 0,07-0,18	80-140 0,07-0,14	130-225 0,07-0,18	- -	- -	- -	10 Δ	15,34	...5824
SCET 09T308	UD 9035 	v _c m/min f mm/rev.	140-240 0,08-0,2	80-140 0,08-0,15	130-225 0,08-0,2	- -	- -	- -	10 Δ	16,39	...5827
SCET 120408	UD 9035 	v _c m/min f mm/rev.	140-240 0,09-0,22	80-140 0,09-0,17	130-225 0,09-0,22	- -	- -	- -	10 Δ	20,00	...5830

Δ Solo es posible la entrega de una unidad de embalaje completa.

(W284)