


Plaquita de corte de roscado ISO, interior, 60° métrica, perfil macizo




2.5

Designación ISO	Tipo de material de corte	Velocidad de corte						H templado	U.E.	format		Ref.
			P acero	M inoxidable	K fundición	N aluminio	S superaleac.			2969	€	
11 NR 050	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,81	...0900	
11 NR 075	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,81	...0903	
11 NR 100	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,81	...0906	
11 NL 100	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,81	...0908	
11 NR 125	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,81	...0909	
11 NR 150	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	24,15	...0912	
11 NL 150	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,81	...0913	
16 NR 050	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0915	
16 NR 075	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0918	
16 NR 100	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0921	
16 NL 100	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0922	
16 NR 125	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0924	
16 NR 150	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0927	
16 NL 150	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0928	
16 NR 175	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0930	
16 NR 200	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0933	
16 NL 200	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0934	
16 NR 250	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0936	
16 NR 300	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...0939	

Δ Solo es posible la entrega de una unidad de embalaje completa.

(W288)

Juego de plaquitas de corte de roscado ISO, interior, 60° métrica, perfil macizo



Designación ISO	Tipo de material de corte	Velocidad de corte						H templado	Pieza x paso mm	format		Ref.
			P acero	M inoxidable	K fundición	N aluminio	S superaleac.			2969	€	
11 IR	PK25	v _c m/min	100-150	-	90-125	-	-	-	2 x 0,5; 2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5	143,52	...1300	
11 IL	PK25	v _c m/min	100-150	-	90-125	-	-	-	2 x 0,5; 2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5	143,52	...1305	
16 IR	PK25	v _c m/min	100-150	-	90-125	-	-	-	2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5; 2 x 1,75	143,52	...1310	
16 IL	PK25	v _c m/min	100-150	-	90-125	-	-	-	2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5; 2 x 1,75	143,52	...1315	

(W288)

Plaquita de corte de roscado ISO, interior, 55° WW, perfil macizo



Designación ISO	Tipo de material de corte	Velocidad de corte						H templado	U.E.	format		Ref.
			P acero	M inoxidable	K fundición	N aluminio	S superaleac.			2969	€	
11 NR 140	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	24,15	...2000	
11 NR 190	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	24,15	...2003	
16 NR 100	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	24,63	...2012	
16 NR 110	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,31	...2015	
16 NR 140	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	24,63	...2021	
16 NR 160	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	24,63	...2024	
16 NR 190	U 9035	v _c m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	24,63	...2027	

Δ Solo es posible la entrega de una unidad de embalaje completa.

(W288)