

Llave de percusión de boca fija

Características: DIN 133. Posición de boca 15°.

Aplicación: Para trabajos de montaje especialmente difíciles.

5770 De acero de vanadio GEDORE 31CrV3.

5835 De acero especial de alta aleación, fosfatado.



5770 GEDORE

5835 fortis

| Entrecaras mm | GEDORE | | fortis | | Ref. |
|------------------|--------|--------|--------|------|---------|
| | 5770 | 5835 | 5770 | 5835 | |
| | € | | € | | |
| 27 | 32,18 | 10,89 | | | ...0027 |
| 30 | 36,99 | 13,29 | | | ...0030 |
| 32 | 40,20 | 16,75 | | | ...0032 |
| 36 | 45,04 | 19,03 | | | ...0036 |
| 41 | 56,28 | 26,23 | | | ...0041 |
| 46 | 69,17 | 35,55 | | | ...0046 |
| 50 | 86,87 | 36,02 | | | ...0050 |
| 55 | 104,54 | 46,19 | | | ...0055 |
| 60 | 107,76 | 57,32 | | | ...0060 |
| | (W522) | (W730) | | | |

| Entrecaras mm | GEDORE | | fortis | | Ref. |
|------------------|--------|--------|--------|------|---------|
| | 5770 | 5835 | 5770 | 5835 | |
| | € | | € | | |
| 65 | 128,72 | - | | | ...0065 |
| 70 | 152,85 | - | | | ...0070 |
| 75 | 191,45 | - | | | ...0075 |
| 80 | 207,57 | - | | | ...0080 |
| 85 | 239,74 | - | | | ...0085 |
| 90 | 320,15 | - | | | ...0090 |
| 95 | 352,33 | - | | | ...0095 |
| 100 | 609,78 | - | | | ...0100 |
| | (W522) | (W730) | | | |

Llave de percusión con boca en estrella

Características: DIN 7444.

Aplicación: Para trabajos de montaje especialmente difíciles.

5773 De acero de vanadio GEDORE 31CrV3. Entrecaras de 24 a 60 mm con perfil UnitDrive, a partir de entrecaras de 65 mm con perfil bihexagonal.

5922 StahlwilleSTABIL®, de acero de aleación de cromo.

NEW

5836 De acero especial de alta aleación, fosfatado.



5773 GEDORE



5922 STAHLWILLE®



5836 fortis

| Entrecaras mm | GEDORE | | STAHlwILLE® | | fortis | | Ref. |
|------------------|---------|--------|-------------|-----------|--------|------|---------|
| | 5773 | 5922 | 5922 | 5836 | 5773 | 5836 | |
| | € | | € | | € | | |
| 24 | 32,19 * | - | | 11,63 * | | | ...0024 |
| 27 | 40,20 | - | | 12,81 | | | ...0027 |
| 30 | 48,25 | - | | 12,80 | | | ...0030 |
| 32 | 51,47 | 111,23 | | 16,40 | | | ...0032 |
| 36 | 64,37 | 116,97 | | 21,07 | | | ...0036 |
| 41 | 72,38 | 148,91 | | 20,71 | | | ...0041 |
| 46 | 80,43 | 158,48 | | 30,15 | | | ...0046 |
| 50 | 88,47 | 183,59 | | 36,04 | | | ...0050 |
| 55 | 96,53 | 202,12 | | 40,09 | | | ...0055 |
| 60 | 104,55 | 228,44 | | 44,77 | | | ...0060 |
| 65 | 128,71 | 279,86 | | 57,00 | | | ...0065 |
| 70 | 144,79 | 310,96 | | 61,47 * N | | | ...0070 |
| | (W522) | (W625) | (W625) | (W730) | | | |

* Tamaño no normalizado.

| Entrecaras mm | GEDORE | | STAHlwILLE® | | fortis | | Ref. |
|------------------|--------|----------|-------------|-----------|--------|------|---------|
| | 5773 | 5922 | 5922 | 5836 | 5773 | 5836 | |
| | € | | € | | € | | |
| 75 | 160,88 | 338,47 | | 66,69 * N | | | ...0075 |
| 80 | 239,74 | 468,24 | | - | | | ...0080 |
| 85 | 304,10 | 517,28 | | - | | | ...0085 |
| 90 | 352,34 | 658,40 | | - | | | ...0090 |
| 95 | 400,60 | 742,12 | | - | | | ...0095 |
| 100 | 481,04 | 882,06 | | - | | | ...0100 |
| 105 | 561,50 | 948,43 | | - | | | ...0105 |
| 110 | 609,77 | 1.211,55 | | - | | | ...0110 |
| 115 | 641,92 | 1.267,76 | | - | | | ...0115 |
| 120 | - | 1.571,54 | | - | | | ...0120 |
| | (W522) | (W625) | (W625) | (W730) | | | |