

Punta para tornillos con TORX® interior de 1/4" DIN 3126 E 6,3

Características: De gran dureza.

89 mm



6473

format
professional quality



6455

Wera
DF-A TOOL PERFEKT

Tamaño	Longitud mm	U.E.	format		Ref.
			6473	6455	
			€	€	
T 8	89	10	-	6,28	...0008
T 10	89	10	3,26	8,86	...0010
T 15	89	10	3,26	8,86	...0015
T 20	89	10	3,26	8,86	...0020
T 25	89	10	3,26	8,86	...0025
T 27	89	10	-	6,28	...0027
T 30	89	10	3,26	8,86	...0030
T 40	89	10	-	8,86	...0040

(W546) (W545)

Punta para tornillos con TORX® interior de 1/4" DIN 3126 E 6,3

NEW

Características: De gran dureza.

152 mm



6476

Wera

Tamaño	Longitud mm	U.E.	Wera		Ref.
			6476		
			€		
T 10	152	10	9,27		...0005
T 15	152	10	9,27		...0010
T 20	152	10	9,27		...0015

(W545)

Tamaño	Longitud mm	U.E.	Wera		Ref.
			6476		
			€		
T 25	152	10	9,27		...0020
T 30	152	10	9,27		...0030
T 40	152	10	9,27		...0035

(W545)

Punta para tornillos con TORX® interior de 1/4" con pasador de retención DIN 3126 C 6,3

Características: De gran dureza.

25 mm



6435

format
professional quality



645B

Wera
DF-A TOOL PERFEKT

Tamaño	Longitud mm	U.E.	format		Ref.
			6435	645B	
			€	€	
T 8	25	10	2,03	-	...0003
T 10	25	10	2,03	3,66	...0005
T 15	25	10	2,03	3,66	...0010
T 20	25	10	2,03	3,66	...0015
T 25	25	10	2,03	3,66	...0020
T 27	25	10	2,03	3,66	...0025
T 30	25	10	2,03	3,66	...0030
T 40	25	10	2,03	3,66	...0035

(W546) (W545)

Punta para tornillos con TORX® interior de 1/4" con pasador de retención DIN 3126 E 6,3,

Características: De gran dureza.

89 mm



Tamaño	Longitud mm	U.E.	Wera		Ref.
			6459		
			€		
T 8	89	5	16,79		...0008
T 10	89	5	16,79		...0010
T 15	89	5	16,79		...0015
T 20	89	5	16,79		...0020
T 25	89	5	16,79		...0025
T 30	89	5	16,79		...0030
T 40	89	5	16,79		...0040

(W545)

Punta para tornillos con TORX PLUS® interior de 1/4" DIN 3126 C 6,3

Características: De gran dureza.

25 mm



Tamaño	Longitud mm	U.E.	Wera		Ref.
			6438		
			€		
10 IP	25	10	3,93		...0010
15 IP	25	10	3,93		...0015
20 IP	25	10	3,93		...0020

(W545)

Tamaño	Longitud mm	U.E.	Wera		Ref.
			6438		
			€		
25 IP	25	10	3,93		...0025
30 IP	25	10	3,93		...0030
40 IP	25	10	3,93		...0040

(W545)