


Tobera portatubo roscada con rosca macho

Características: De latón.

Conexión pulgadas	Conexión del tubo flexible mm	E/C mm	Presión de servicio bar	Temperatura de servicio °C	RIEGLER	
					9416 €	Ref.
G 1/8	6	14	25	150	1,50	...0590
G 1/4	6	17	25	150	1,80	...0595
G 3/8	6	19	25	150	1,86	...0600
G 1/4	9	17	25	150	1,80	...0605
G 3/8	9	19	25	150	1,99	...0610
G 1/2	9	24	25	150	3,12	...0615
G 3/8	13	19	25	150	2,36	...0620
G 1/2	13	24	25	150	3,32	...0625
G 3/4	13	32	25	150	6,59	...0630
G 3/4	16	32	25	150	6,59	...0635
G 3/4	19	32	25	150	6,05	...0640

(W971)



Tobera portatubo doble

Características: De latón.

Ø interior del tubo flexible mm	Longitud mm	Presión de servicio bar	Temperatura del medio °C	RIEGLER	
				9416 €	Ref.
6	55	16	90	2,12	...0646
9	55	16	90	2,41	...0651
13	55	16	90	3,38	...0656

(W971)




Tobera doble con rosca macho

Características: De latón.

Conexión pulgadas	E/C mm	Presión de servicio bar	Temperatura de servicio °C	RIEGLER	
				9416 €	Ref.
G 1/8 x G 1/8	14	25	150	1,15	...0660
G 1/4 x G 1/4	17	25	150	1,32	...0665
G 3/8 x G 3/8	19	25	150	1,50	...0670
G 1/2 x G 1/2	24	25	150	2,77	...0675
G 3/4 x G 3/4	32	25	150	6,20	...0680
G 1/8 x G 1/4	17	25	150	1,41	...0685
G 1/4 x G 3/8	19	25	150	1,73	...0690
G 3/8 x G 1/2	24	25	150	3,12	...0695
G 1/2 x G 3/4	32	25	150	3,99	...0700

(W971)



Manguito con rosca hembra

Características: De latón con rosca pasante.

Conexión pulgadas	E/C mm	Presión de servicio bar	Temperatura de servicio °C	RIEGLER	
				9416 €	Ref.
G 1/8	14	25	150	1,32	...0711
G 1/4	17	25	150	1,69	...0716
G 3/8	22	25	150	2,36	...0721
G 1/2	27	25	150	3,53	...0726
G 3/4	32	25	150	6,24	...0731

(W971)




Pieza en T

Características: De latón, con rosca macho (RM) y rosca hembra (RH). La rosca hembra es cilíndrica conforme a DIN EN ISO 228-1 y la rosca macho es cónica conforme a DIN 2999.

9416 0735 Con rosca macho.
- 0745

Conexión pulgadas	E/C mm	Presión de servicio bar	Temperatura de servicio °C	RIEGLER	
				9416 €	Ref.
R 1/4	13	60	150	4,31	...0735
R 3/8	17	60	150	6,22	...0740
R 1/2	21	60	150	8,95	...0745

(W971)




9416 0735-0745

9416 0750 Con rosca hembra.
- 0760

Conexión pulgadas	E/C mm	Presión de servicio bar	Temperatura de servicio °C	RIEGLER	
				9416 €	Ref.
G 1/4	13	60	150	5,01	...0750
G 3/8	17	60	150	7,11	...0755
G 1/2	21	60	150	9,27	...0760

(W971)



9416 0750-0760