

Piezas individual y complementaria 1/4"

				LOC-LINE®	
					
				9600	Ref.
Características		Dimensiones	Índice Pieza	€	
	Manguera flexible articulada (10 piezas articuladas)	147 mm	2	9,95	...0006
	Manguera flexible articulada	1,5 m	1	56,49	...0007
	Codo de manguera flexible 90°	70 mm	4	24,21	...0008
	Sistema de anilla (15 segmentos + 1 caperuza de cierre)	446 mm	1	51,21	...0009
	Tobera redonda	∅ 1,5 mm	4	8,03	...0011
	Tobera redonda	∅ 3,0 mm	4	8,03	...0016
	Tobera redonda	∅ 6,0 mm	4	8,03	...0021
	Tobera plana	25 mm	2	9,55	...0026
	Tobera de rectificar	25 mm	2	12,23	...0031
	Tobera articulada tipo ducha	16 orificios de ∅ 1,0 mm	2	23,17	...0037
	Tobera articulada tipo ducha	16 orificios de ∅ 1,5 mm	2	23,17	...0038
	Tobera articulada tipo ducha	20 orificios de ∅ 2,0 mm	2	25,45	...0039
	Racor	R 1/8"	4	8,03	...0036
	Racor	R 1/4"	4	8,03	...0041
	Distribuidor en Y	1/4"	2	9,53	...0046
	Llave de cierre para tubo articulado	1/4"	2	18,79	...0051
	Llave de cierre con rosca macho	1/4"	2	18,79	...0056
	Llave de cierre con rosca hembra	1/4"	2	18,79	...0061
	Válvula de retención	1/4"	2	19,87	...0066
	Conexión angular	1/4"	2	11,26	...0071
	Distribuidor en T	1/4"	2	11,74	...0076
	Anillo de abrazadera	1/4"	4	13,96	...0088
	Alicates de montaje	1/4"	1	22,71	...0081

(W991)