

Avellanador de espiga tamaño 2



| Ø de avellana- do (K8) D mm | Ø de vástago mm | Longitud total mm | Longi- tud de cabezal mm | Longi- tud de vástago mm | Ø de per- foración mm | afs | |
|-----------------------------------|-----------------------|-------------------------|-----------------------------------|-----------------------------------|-----------------------------|-------------|---------|
| | | | | | | 1489 € | Ref. |
| 24 | 22 | 60 | 27 | 33 | 10 | 130,83 | ...2400 |
| 24.5 | 22 | 60 | 27 | 33 | 10 | 130,83 | ...2450 |
| 25 | 22 | 60 | 27 | 33 | 10 | 130,83 | ...2500 |
| 25.5 | 22 | 60 | 27 | 33 | 10 | a consultar | ...2550 |
| 26 | 22 | 60 | 27 | 33 | 10 | 148,28 | ...2600 |
| 26.5 | 22 | 60 | 27 | 33 | 10 | 148,28 | ...2650 |
| 27 | 22 | 60 | 27 | 33 | 10 | 148,28 | ...2700 |
| 27.5 | 22 | 60 | 27 | 33 | 10 | 148,28 | ...2750 |
| 28 | 22 | 60 | 27 | 33 | 10 | 150,84 | ...2800 |
| 28.5 | 22 | 60 | 27 | 33 | 10 | 150,84 | ...2850 |
| 29 | 22 | 60 | 27 | 33 | 10 | 150,84 | ...2900 |
| 29.5 | 22 | 60 | 27 | 33 | 10 | 150,84 | ...2950 |
| 30 | 22 | 60 | 27 | 33 | 10 | 154,47 | ...3000 |
| 30.5 | 22 | 60 | 27 | 33 | 10 | 154,47 | ...3050 |
| 31 | 22 | 60 | 27 | 33 | 10 | 154,47 | ...3100 |
| 32 | 22 | 60 | 27 | 33 | 10 | 154,47 | ...3200 |
| 33 | 22 | 60 | 27 | 33 | 10 | 162,07 | ...3300 |
| 34 | 22 | 60 | 27 | 33 | 10 | 162,07 | ...3400 |
| 35 | 22 | 60 | 27 | 33 | 10 | 162,07 | ...3500 |
| 36 | 22 | 60 | 27 | 33 | 10 | 162,07 | ...3600 |
| 37 | 22 | 60 | 27 | 33 | 10 | 196,88 | ...3700 |
| 38 | 22 | 60 | 27 | 33 | 10 | 196,88 | ...3800 |
| 39 | 22 | 60 | 27 | 33 | 10 | 196,88 | ...3900 |
| 40 | 22 | 60 | 27 | 33 | 10 | 196,88 | ...4000 |
| 41 | 22 | 60 | 27 | 33 | 10 | 268,08 | ...4100 |

Disponibles hasta Ø 85 mm.

(W138)

| Ø de avellana- do (K8) D mm | Ø de vástago mm | Longitud total mm | Longi- tud de cabezal mm | Longi- tud de vástago mm | Ø de per- foración mm | afs | |
|-----------------------------------|-----------------------|-------------------------|-----------------------------------|-----------------------------------|-----------------------------|-------------|---------|
| | | | | | | 1489 € | Ref. |
| 42 | 22 | 60 | 27 | 33 | 10 | 268,08 | ...4200 |
| 43 | 22 | 60 | 27 | 33 | 10 | 268,08 | ...4300 |
| 44 | 22 | 60 | 27 | 33 | 10 | 268,08 | ...4400 |
| 45 | 22 | 60 | 27 | 33 | 10 | 278,68 | ...4500 |
| 46 | 22 | 60 | 27 | 33 | 10 | 278,68 | ...4600 |
| 47 | 22 | 60 | 27 | 33 | 10 | 278,68 | ...4700 |
| 48 | 22 | 60 | 27 | 33 | 10 | 278,68 | ...4800 |
| 49 | 22 | 60 | 27 | 33 | 10 | a consultar | ...4900 |
| 50 | 22 | 60 | 27 | 33 | 10 | 354,40 | ...5000 |
| 51 | 22 | 60 | 27 | 33 | 10 | 355,91 | ...5100 |
| 52 | 22 | 60 | 27 | 33 | 10 | 355,91 | ...5200 |
| 53 | 22 | 60 | 27 | 33 | 10 | 395,29 | ...5300 |
| 54 | 22 | 60 | 27 | 33 | 10 | 395,29 | ...5400 |
| 55 | 22 | 60 | 27 | 33 | 10 | 395,29 | ...5500 |
| 56 | 22 | 60 | 27 | 33 | 10 | 395,29 | ...5600 |
| 57 | 22 | 60 | 27 | 33 | 10 | a consultar | ...5700 |
| 58 | 22 | 60 | 27 | 33 | 10 | 448,29 | ...5800 |
| 60 | 22 | 60 | 27 | 33 | 10 | 448,29 | ...6000 |
| 62 | 22 | 60 | 27 | 33 | 10 | 448,29 | ...6200 |
| 64 | 22 | 60 | 27 | 33 | 10 | a consultar | ...6400 |
| 65 | 22 | 60 | 27 | 33 | 10 | 448,29 | ...6500 |
| 66 | 22 | 60 | 27 | 33 | 10 | 448,29 | ...6600 |

(W138)

Espiga de guía tamaño 01

Fija sin refrigeración interior.



| Ø de espiga (e8) D mm | Ø de vástago mm | Longitud total mm | Longi- tud de cabezal mm | afs | |
|-----------------------------|--------------------|----------------------|-----------------------------------|-------------|---------|
| | | | | 1479 € | Ref. |
| 2.4 | 2.4 | 40 | 6 | 28,91 | ...0240 |
| 2.5 | 2.4 | 40 | 6 | a consultar | ...0250 |
| 2.6 | 2.4 | 40 | 6 | a consultar | ...0260 |
| 2.7 | 2.4 | 40 | 6 | a consultar | ...0270 |
| 2.8 | 2.4 | 40 | 6 | a consultar | ...0280 |
| 2.9 | 2.4 | 40 | 6 | 28,91 | ...0290 |
| 3 | 2.4 | 40 | 6 | 28,91 | ...0300 |
| 3.1 | 2.4 | 40 | 6 | 28,91 | ...0310 |
| 3.2 | 2.4 | 40 | 6 | 28,91 | ...0320 |
| 3.3 | 2.4 | 40 | 6 | 28,91 | ...0330 |
| 3.4 | 2.4 | 40 | 6 | 28,91 | ...0340 |

(W138)

| Ø de espiga (e8) D mm | Ø de vástago mm | Longitud total mm | Longi- tud de cabezal mm | afs | |
|-----------------------------|--------------------|----------------------|-----------------------------------|-------------|---------|
| | | | | 1479 € | Ref. |
| 3.5 | 2.4 | 40 | 6 | 28,91 | ...0350 |
| 3.6 | 2.4 | 40 | 6 | a consultar | ...0360 |
| 3.7 | 2.4 | 40 | 6 | a consultar | ...0370 |
| 3.8 | 2.4 | 40 | 6 | a consultar | ...0380 |
| 3.9 | 2.4 | 40 | 6 | 28,91 | ...0390 |
| 4 | 2.4 | 40 | 6 | 28,91 | ...0400 |
| 4.1 | 2.4 | 40 | 6 | 28,91 | ...0410 |
| 4.2 | 2.4 | 40 | 6 | 28,91 | ...0420 |
| 4.3 | 2.4 | 40 | 6 | a consultar | ...0430 |
| 4.4 | 2.4 | 40 | 6 | 28,91 | ...0440 |
| 4.5 | 2.4 | 40 | 6 | 28,91 | ...0450 |

(W138)

Espiga de guía tamaño 0

Fija sin refrigeración interior.



| Ø de espiga (e8) D mm | Ø de vástago mm | Longitud total mm | Longitud de cabezal mm | afs | |
|--------------------------|-----------------------|----------------------|------------------------------|-------------|---------|
| | | | | 1483 € | Ref. |
| 4 | 4 | 59 | 9 | 19,99 | ...0400 |
| 4.1 | 4 | 59 | 9 | 19,99 | ...0410 |
| 4.2 | 4 | 59 | 9 | 19,99 | ...0420 |
| 4.3 | 4 | 59 | 9 | a consultar | ...0430 |
| 4.5 | 4 | 59 | 9 | 19,99 | ...0450 |
| 4.8 | 4 | 59 | 9 | 19,99 | ...0480 |

(W138)

| Ø de espiga (e8) D mm | Ø de vástago mm | Longitud total mm | Longitud de cabezal mm | afs | |
|--------------------------|-----------------------|----------------------|------------------------------|-----------|---------|
| | | | | 1483 € | Ref. |
| 4.9 | 4 | 59 | 9 | 19,99 | ...0490 |
| 5 | 4 | 59 | 9 | 19,99 | ...0500 |
| 5.3 | 4 | 59 | 9 | 19,99 | ...0530 |
| 5.5 | 4 | 59 | 9 | 21,94 | ...0550 |
| 5.8 | 4 | 59 | 9 | 21,94 | ...0580 |
| 5.9 | 4 | 59 | 9 | 21,94 | ...0590 |

(W138)

Continúa en la página siguiente