

Avellanador de espiga tamaño 2



Ø de avellana- do (K8) D mm	Ø de vástago mm	Longitud total mm	Longi- tud de cabezal mm	Longi- tud de vástago mm	Ø de per- foración mm	afs	
						1489 €	Ref.
24	22	60	27	33	10	130,83	...2400
24.5	22	60	27	33	10	130,83	...2450
25	22	60	27	33	10	130,83	...2500
25.5	22	60	27	33	10	a consultar	...2550
26	22	60	27	33	10	148,28	...2600
26.5	22	60	27	33	10	148,28	...2650
27	22	60	27	33	10	148,28	...2700
27.5	22	60	27	33	10	148,28	...2750
28	22	60	27	33	10	150,84	...2800
28.5	22	60	27	33	10	150,84	...2850
29	22	60	27	33	10	150,84	...2900
29.5	22	60	27	33	10	150,84	...2950
30	22	60	27	33	10	154,47	...3000
30.5	22	60	27	33	10	154,47	...3050
31	22	60	27	33	10	154,47	...3100
32	22	60	27	33	10	154,47	...3200
33	22	60	27	33	10	162,07	...3300
34	22	60	27	33	10	162,07	...3400
35	22	60	27	33	10	162,07	...3500
36	22	60	27	33	10	162,07	...3600
37	22	60	27	33	10	196,88	...3700
38	22	60	27	33	10	196,88	...3800
39	22	60	27	33	10	196,88	...3900
40	22	60	27	33	10	196,88	...4000
41	22	60	27	33	10	268,08	...4100

Disponibles hasta Ø 85 mm.

(W138)

Ø de avellana- do (K8) D mm	Ø de vástago mm	Longitud total mm	Longi- tud de cabezal mm	Longi- tud de vástago mm	Ø de per- foración mm	afs	
						1489 €	Ref.
42	22	60	27	33	10	268,08	...4200
43	22	60	27	33	10	268,08	...4300
44	22	60	27	33	10	268,08	...4400
45	22	60	27	33	10	278,68	...4500
46	22	60	27	33	10	278,68	...4600
47	22	60	27	33	10	278,68	...4700
48	22	60	27	33	10	278,68	...4800
49	22	60	27	33	10	a consultar	...4900
50	22	60	27	33	10	354,40	...5000
51	22	60	27	33	10	355,91	...5100
52	22	60	27	33	10	355,91	...5200
53	22	60	27	33	10	395,29	...5300
54	22	60	27	33	10	395,29	...5400
55	22	60	27	33	10	395,29	...5500
56	22	60	27	33	10	395,29	...5600
57	22	60	27	33	10	a consultar	...5700
58	22	60	27	33	10	448,29	...5800
60	22	60	27	33	10	448,29	...6000
62	22	60	27	33	10	448,29	...6200
64	22	60	27	33	10	a consultar	...6400
65	22	60	27	33	10	448,29	...6500
66	22	60	27	33	10	448,29	...6600

(W138)

Espiga de guía tamaño 01

Fija sin refrigeración interior.



Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longi- tud de cabezal mm	afs	
				1479 €	Ref.
2.4	2.4	40	6	28,91	...0240
2.5	2.4	40	6	a consultar	...0250
2.6	2.4	40	6	a consultar	...0260
2.7	2.4	40	6	a consultar	...0270
2.8	2.4	40	6	a consultar	...0280
2.9	2.4	40	6	28,91	...0290
3	2.4	40	6	28,91	...0300
3.1	2.4	40	6	28,91	...0310
3.2	2.4	40	6	28,91	...0320
3.3	2.4	40	6	28,91	...0330
3.4	2.4	40	6	28,91	...0340

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longi- tud de cabezal mm	afs	
				1479 €	Ref.
3.5	2.4	40	6	28,91	...0350
3.6	2.4	40	6	a consultar	...0360
3.7	2.4	40	6	a consultar	...0370
3.8	2.4	40	6	a consultar	...0380
3.9	2.4	40	6	28,91	...0390
4	2.4	40	6	28,91	...0400
4.1	2.4	40	6	28,91	...0410
4.2	2.4	40	6	28,91	...0420
4.3	2.4	40	6	a consultar	...0430
4.4	2.4	40	6	28,91	...0440
4.5	2.4	40	6	28,91	...0450

(W138)

Espiga de guía tamaño 0

Fija sin refrigeración interior.



Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1483 €	Ref.
4	4	59	9	19,99	...0400
4.1	4	59	9	19,99	...0410
4.2	4	59	9	19,99	...0420
4.3	4	59	9	a consultar	...0430
4.5	4	59	9	19,99	...0450
4.8	4	59	9	19,99	...0480

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1483 €	Ref.
4.9	4	59	9	19,99	...0490
5	4	59	9	19,99	...0500
5.3	4	59	9	19,99	...0530
5.5	4	59	9	21,94	...0550
5.8	4	59	9	21,94	...0580
5.9	4	59	9	21,94	...0590

(W138)

Continúa en la página siguiente

Espiga de guía tamaño 0

Continuado de la página anterior

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1483 €	Ref.
6	4	59	9	21,94	...0600
6.1	4	59	9	21,94	...0610
6.4	4	59	9	21,94	...0640
6.5	4	59	9	21,94	...0650
6.6	4	59	9	21,94	...0660
6.7	4	59	9	21,94	...0670
6.8	4	59	9	21,94	...0680
6.9	4	59	9	21,94	...0690
7	4	59	9	22,56	...0700
7.4	4	59	9	22,56	...0740
7.5	4	59	9	22,56	...0750
7.6	4	59	9	22,56	...0760
7.8	4	59	9	22,56	...0780
7.9	4	59	9	22,56	...0790

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1483 €	Ref.
8	4	59	9	22,56	...0800
8.2	4	59	9	22,56	...0820
8.4	4	59	9	22,56	...0840
8.5	4	59	9	22,56	...0850
9	4	59	9	22,56	...0900
9.5	4	59	9	23,19	...0950
9.9	4	59	9	23,19	...0990
10	4	59	9	23,19	...1000
10.2	4	59	9	23,19	...1020
10.5	4	59	9	23,19	...1050
11	4	59	9	23,19	...1100
11.5	4	59	9	23,19	...1150

(W138)

Espiga de guía tamaño 1

Ø 6,6-8,4 mm., fija sin refrigeración interior.
Ø 8,5-18,0 mm., rotativa y con refrigeración interior.



Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1487 €	Ref.
6.6	6	79	15	22,56	...0660
6.7	6	79	15	a consultar	...0670
6.8	6	79	15	22,56	...0680
6.9	6	79	15	22,56	...0690
7	6	79	15	22,56	...0700
7.4	6	79	15	a consultar	...0740
7.5	6	79	15	22,56	...0750
7.6	6	79	15	a consultar	...0760
7.8	6	79	15	22,56	...0780
7.9	6	79	15	22,56	...0790
8	6	79	15	24,38	...0800
8.2	6	79	15	a consultar	...0820
8.4	6	79	15	24,38	...0840
8.5	6	79	15	27,72	...0850
9	6	79	15	27,72	...0900
9.5	6	79	15	27,72	...0950
9.9	6	79	15	28,15	...0990
10	6	79	15	28,15	...1000
10.2	6	79	15	28,15	...1020

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1487 €	Ref.
10.5	6	79	15	28,15	...1050
11	6	79	15	28,15	...1100
11.5	6	79	15	28,15	...1150
12	6	79	15	28,15	...1200
12.5	6	79	15	30,59	...1250
13	6	79	15	30,59	...1300
13.5	6	79	15	30,59	...1350
14	6	79	15	30,59	...1400
14.5	6	79	15	30,59	...1450
15	6	79	15	30,59	...1500
15.5	6	79	15	a consultar	...1550
16	6	79	15	31,95	...1600
16.5	6	79	15	31,95	...1650
17	6	79	15	31,95	...1700
17.5	6	79	15	31,95	...1750
18	6	79	15	31,95	...1800

(W138)

Espiga de guía tamaño 2

Ø 10,0-13,5 mm., fija sin refrigeración interior.
Ø 14,0-40,0 mm., rotativa y con refrigeración interior.



Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1491 €	Ref.
10	10	105	18	36,35	...1000
10.2	10	105	18	36,35	...1020
10.5	10	105	18	36,35	...1050
11	10	105	18	36,35	...1100
11.5	10	105	18	36,35	...1150
12	10	105	18	36,35	...1200
12.5	10	105	18	36,35	...1250
13	10	105	18	36,35	...1300
13.5	10	105	18	36,35	...1350
14	10	105	18	42,26	...1400
14.5	10	105	18	42,26	...1450
15	10	105	18	42,26	...1500

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1491 €	Ref.
15.5	10	105	18	42,26	...1550
16	10	105	18	42,26	...1600
16.5	10	105	18	43,94	...1650
17	10	105	18	43,94	...1700
17.5	10	105	18	43,94	...1750
18	10	105	18	43,94	...1800
18.5	10	105	18	43,94	...1850
19	10	105	18	45,14	...1900
19.5	10	105	18	45,14	...1950
20	10	105	18	45,14	...2000
20.5	10	105	18	45,14	...2050
21	10	105	18	45,14	...2100

(W138)

Continúa en la página siguiente