

### Espiga de guía tamaño 0

Continuado de la página anterior

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1483 €	Ref.
6	4	59	9	21,94	...0600
6.1	4	59	9	21,94	...0610
6.4	4	59	9	21,94	...0640
6.5	4	59	9	21,94	...0650
6.6	4	59	9	21,94	...0660
6.7	4	59	9	21,94	...0670
6.8	4	59	9	21,94	...0680
6.9	4	59	9	21,94	...0690
7	4	59	9	22,56	...0700
7.4	4	59	9	22,56	...0740
7.5	4	59	9	22,56	...0750
7.6	4	59	9	22,56	...0760
7.8	4	59	9	22,56	...0780
7.9	4	59	9	22,56	...0790

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1483 €	Ref.
8	4	59	9	22,56	...0800
8.2	4	59	9	22,56	...0820
8.4	4	59	9	22,56	...0840
8.5	4	59	9	22,56	...0850
9	4	59	9	22,56	...0900
9.5	4	59	9	23,19	...0950
9.9	4	59	9	23,19	...0990
10	4	59	9	23,19	...1000
10.2	4	59	9	23,19	...1020
10.5	4	59	9	23,19	...1050
11	4	59	9	23,19	...1100
11.5	4	59	9	23,19	...1150

(W138)

### Espiga de guía tamaño 1

Ø 6,6-8,4 mm., fija sin refrigeración interior.  
Ø 8,5-18,0 mm., rotativa y con refrigeración interior.



Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1487 €	Ref.
6.6	6	79	15	22,56	...0660
6.7	6	79	15	a consultar	...0670
6.8	6	79	15	22,56	...0680
6.9	6	79	15	22,56	...0690
7	6	79	15	22,56	...0700
7.4	6	79	15	a consultar	...0740
7.5	6	79	15	22,56	...0750
7.6	6	79	15	a consultar	...0760
7.8	6	79	15	22,56	...0780
7.9	6	79	15	22,56	...0790
8	6	79	15	24,38	...0800
8.2	6	79	15	a consultar	...0820
8.4	6	79	15	24,38	...0840
8.5	6	79	15	27,72	...0850
9	6	79	15	27,72	...0900
9.5	6	79	15	27,72	...0950
9.9	6	79	15	28,15	...0990
10	6	79	15	28,15	...1000
10.2	6	79	15	28,15	...1020

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1487 €	Ref.
10.5	6	79	15	28,15	...1050
11	6	79	15	28,15	...1100
11.5	6	79	15	28,15	...1150
12	6	79	15	28,15	...1200
12.5	6	79	15	30,59	...1250
13	6	79	15	30,59	...1300
13.5	6	79	15	30,59	...1350
14	6	79	15	30,59	...1400
14.5	6	79	15	30,59	...1450
15	6	79	15	30,59	...1500
15.5	6	79	15	a consultar	...1550
16	6	79	15	31,95	...1600
16.5	6	79	15	31,95	...1650
17	6	79	15	31,95	...1700
17.5	6	79	15	31,95	...1750
18	6	79	15	31,95	...1800

(W138)

### Espiga de guía tamaño 2

Ø 10,0-13,5 mm., fija sin refrigeración interior.  
Ø 14,0-40,0 mm., rotativa y con refrigeración interior.



Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1491 €	Ref.
10	10	105	18	36,35	...1000
10.2	10	105	18	36,35	...1020
10.5	10	105	18	36,35	...1050
11	10	105	18	36,35	...1100
11.5	10	105	18	36,35	...1150
12	10	105	18	36,35	...1200
12.5	10	105	18	36,35	...1250
13	10	105	18	36,35	...1300
13.5	10	105	18	36,35	...1350
14	10	105	18	42,26	...1400
14.5	10	105	18	42,26	...1450
15	10	105	18	42,26	...1500

(W138)

Ø de espiga (e8) D mm	Ø de vástago mm	Longitud total mm	Longitud de cabezal mm	afs	
				1491 €	Ref.
15.5	10	105	18	42,26	...1550
16	10	105	18	42,26	...1600
16.5	10	105	18	43,94	...1650
17	10	105	18	43,94	...1700
17.5	10	105	18	43,94	...1750
18	10	105	18	43,94	...1800
18.5	10	105	18	43,94	...1850
19	10	105	18	45,14	...1900
19.5	10	105	18	45,14	...1950
20	10	105	18	45,14	...2000
20.5	10	105	18	45,14	...2050
21	10	105	18	45,14	...2100

(W138)

Continúa en la página siguiente