

Fresa con mango HSS (fresa rotativa) Ø de vástago 6 mm, dentado 3

Continuación

2624 Forma cónica de punta redondeada L

Forma	Ø del cabezal mm	Longi- tud de cabezal mm	Ángulo °	Radio mm	Longitud total mm	2624	Ref.
						€	
L 1020	10	20	14	2,9	60	23,02	...0000
L 1230	12	30	14	2,6	70	27,13	...0005
L 1630	16	30	14	4,8	70	34,80	...0010

(W236)

2626 Forma de gota O

Forma	Ø del cabezal mm	Longitud de cabezal mm	Radio mm	Longitud total mm	2626	Ref.
					€	
O 1220	12	20	5,0	60	24,40	...0005
O 1625	16	25	6,5	65	34,80	...0010

(W236)

2630 Forma esférica F

Forma	Ø del cabezal mm	Longitud de cabezal mm	Longitud total mm	2630	Ref.
				€	
F 0403	4	3,6	55	12,97	...0005
F 0605	6	5,4	55	13,40	...0010
F 0807	8	7,0	55	20,95	...0015
F 1009	10	9,0	49	24,40	...0020
F 1210	12	10,8	51	29,23	...0025
F 1614	16	41,3	54	34,80	...0030

(W236)

2636 Forma cónica apuntada G

Forma	Ø del cabezal mm	Longitud de cabezal mm	Ángulo °	Longitud total mm	2636	Ref.
					€	
G 0618	6	18	14	60	12,60	...0005
G 1020	10	20	28	60	20,95	...0010
G 1225	12	25	27	65	27,13	...0015

(W236)

2640 Forma de maza HSS 64

Tipo	Ø máximo de la cabeza mm	Longitud de cabezal mm	Longitud total mm	2640	Ref.
				€	
HSS 64	12	30	70	29,52	...0005

(W236)

2641 Forma angular HSS 63ST, con dentado frontal

Tipo	Ø máximo de la cabeza mm	Ø menor de la cabeza mm	Longi- tud de cabezal mm	Ángulo °	Longitud total mm	2641	Ref.
						€	
HSS 63ST	12	8	30	7	70	27,78	...0005

(W105)

