

Plaquita de corte de roscado ISO, interior, 60° métrica, perfil macizo



2.5

Designación ISO	Tipo de material de corte	Velocidad de corte	Material					H templado	U.E.	format	
			P acero	M inoxidable	K fundición	N aluminio	S superaleac.			2969 €	Ref.
11 NR 050	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,00	...0900
11 NR 075	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,00	...0903
11 NR 100	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,00	...0906
11 NL 100	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,00	...0908
11 NR 125	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,00	...0909
11 NR 150	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,27	...0912
11 NL 150	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,00	...0913
16 NR 050	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0915
16 NR 075	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0918
16 NR 100	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0921
16 NL 100	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0922
16 NR 125	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0924
16 NR 150	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0927
16 NL 150	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0928
16 NR 175	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0930
16 NR 200	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0933
16 NL 200	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0934
16 NR 250	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0936
16 NR 300	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...0939

Δ Solo es posible la entrega de una unidad de embalaje completa.

(W105)

Juego de plaquitas de corte de roscado ISO, interior, 60° métrica, perfil macizo



Designación ISO	Tipo de material de corte	Velocidad de corte	Material					H templado	Pieza x paso mm	format	
			P acero	M inoxidable	K fundición	N aluminio	S superaleac.			2969 €	Ref.
11 IR	PK25	v <sub>c</sub> m/min	100-150	-	90-125	-	-	-	2 x 0,5; 2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5	132,07	...1300
11 IL	PK25	v <sub>c</sub> m/min	100-150	-	90-125	-	-	-	2 x 0,5; 2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5	132,07	...1305
16 IR	PK25	v <sub>c</sub> m/min	100-150	-	90-125	-	-	-	2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5; 2 x 1,75	132,07	...1310
16 IL	PK25	v <sub>c</sub> m/min	100-150	-	90-125	-	-	-	2 x 0,75; 2 x 1,0; 2 x 1,25; 2 x 1,5; 2 x 1,75	132,07	...1315

(W105)

Plaquita de corte de roscado ISO, interior, 55° WW, perfil macizo



Designación ISO	Tipo de material de corte	Velocidad de corte	Material					H templado	U.E.	format	
			P acero	M inoxidable	K fundición	N aluminio	S superaleac.			2969 €	Ref.
11 NR 140	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,27	...2000
11 NR 190	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,27	...2003
16 NR 100	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,77	...2012
16 NR 110	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	22,47	...2015
16 NR 140	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,77	...2021
16 NR 160	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,77	...2024
16 NR 190	U 9035	v <sub>c</sub> m/min	135-165	80-95	125-155	200-575	25-45	25-30	10 Δ	23,77	...2027

Δ Solo es posible la entrega de una unidad de embalaje completa.

(W105)